SECRET DOWN					Project:	Туре:
DUS200	Grey				Cat. No.:	
DUS201	White					
DUS200B Black						
LED Surface wall luminaire. Direct, indirect down sconce. Driver included.						
FIXTURE: Mounting: surface wall Finish: Grey, White and Black Finishes are "powder coat". Material: Aluminum Wet Location Listed (for use indoors and outdoors) CSA/US Listed						
LAMP/LED SOURCE/COLOR TEMP: -930 1x3W LED / 3000K / CRI ≥ 90 / 1x260Im Efficacy (CRI ≥ 90): 86Im/W, Rated life > 50000hrs						
<u>DRIVER</u> : -120V/277V-DRV Class 2 120V-277Vac 60Hz not dimmable, Power factor ≥ 0.9 / Flicker (THD) ≤ 20%, Constant current 350mA						
photometric available on	files, dimming c line at <u>www.dlsli</u>	ompatibility i ightingus.com	list and warrar <u>n</u>	nty information	Shown above: DUS201-wi	hite-1x3W-930-120V/277V-DRV
Measurements (Inches)					Light Distribution	
<b>4</b> " <b>4</b> " <b>4</b> " <b>4</b> "					120° 90° 60° 60° 60° 60° 60° 60° 60° 60° 60° 6	180° -420 -140 -140 -280 -140 -280 -140 -280 -140 -280 -140 -280 -140 -280 -1000lm
ORDERING INFORMATION -SUFFIX						
Model Number	Finish	LED Source	Color Temp.	Driver		
DUS200	-grey					
DUS201 DUS200B	-white -black	-1x3W	-930	-120V/277V-DRV		
-	-Diack					
Exan	nple of Catalog	#: DUS200-g	rey-1x3W-930	)-120V/277V-DRV	1	
DLS Lighting 3135 SR 580 Safety Harbo www.dlslight <u>dlsus@dlslig</u>	), Suite 6 or, FL 34695 ingus.com			20	3381 <b>D</b> ®	*DLS